
Meridian 1

Feature Group D

Description and operation

Document Number: 553-2901-102

Document Release: Standard 2.0

Date: December 1994

© 1991, 1994

All rights reserved

Printed in the United States of America

Information is subject to change without notice. Northern Telecom reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant. This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC rules.

SL-1 and Meridian 1 are trademarks of Northern Telecom.

Revision history

December 1, 1991

Standard, release 1.0. This is a new document issued for X11 release 17.

December 1994

Standard, release 2.0. This document is reissued for updates and changes resulting from X11 release 20. Changes are noted with revision bars in the margin.

Contents

Introduction	1
Other documentation	1
Required packages	2
Description	3
Local network and end office switching	3
Originating features	5
Domestic dialing plan	5
Presubscription	5
Service Access Code	6
Automatic Number Identification (ANI)	6
Signaling protocol	7
Carrier test lines	7
Outpulsing	7
Terminating features	7
LEC test lines	7
Interface protocol	8
Direction	8
Signaling protocol	8
Carrier classification	10
Call categories and pulsing formats	11
EANA protocol specifications	14
LEC-to-carrier pulsing	14
Variations	15
Alternative arrangements	16
Time limits	16

EANA protocol example	17
Terminating protocol example	18
Hardware	19
Trunks	19
MF signaling	19
MF senders	19
MF receivers	20
Feature interactions	23
Access restriction	23
Barge-In	28
Call Detail Recording (CDR)	28
Calling Line ID (CLID)	28
Call Party Disconnect Control (CPDC)	28
Call Party Name Display (CPND)	28
Customer Controlled Routing (CCR)	28
Dialled Number Identification Service (DNIS)	29
Digit Display	29
Incoming Digit Conversion (IDC)	30
ISDN PRI and ISL	30
Network Alternate Route Selection (NARS)	30
Network Call Redirection (NCRD)	30
Malicious Call Trace (MCT)	30
Minor Alarm	30
Private Line Service	30
Traffic measurements	31
Trunk Group Distinctive Ringing	31
Trunk Verification from a Station (TVS)	31
Feature operation	33
Example of using the FGD feature	33
How to initiate a call	33
Incoming call routing	34
Incoming call processing	34
Local termination	36
Calls inside World Zone 1 (7 digits)	36
Calls inside World Zone 1 (10 digits)	36

Calls inside World Zone 1 (0+ and 0-)	37
Information digits screening for incoming calls	39
FGD call intercept	40
Incoming test calls (3 and 7 digits)	40
Authorization Code prompting	42
LEC trunk grouping and ANI provision by call category	42
ANI digits screening	43
ANI digits as Calling Line ID (CLID)	45
ANI display	46
ANI number display devices	46
Dial pulse dialing on FGD trunks	47
Outgoing test calls	47
CDR records	47
Transmission characteristics	47
Operating parameters	48
Parameters	48
MF Receiver guidelines	49
Implementation	55
Engineering guidelines	55
Maintenance and diagnostics	67
LD 34—Tone and digital switch	68
LD 30—Network and signaling diagnostics	70
LD 32—Network peripheral equipment diagnostics	70
List of terms	71

List of figures

Figure 1	
Configuration example	4
Figure 2	
Trunk verification	32

List of tables

Table 1	
Call categories	11
Table 2	
Interface protocols	12
Table 3	
Access North American signaling	13
Table 4	
Terminating protocols	14
Table 5	
Information digits (II)	15
Table 6	
EANA protocol: customer dials a World Zone 1 number	17
Table 7	
Terminating protocol: carrier call to an LEC test line	18
Table 8	
MFR specifications	20
Table 9	
Access summary from FGD trunks	23
Table 10	
Restricted access summary from FGD trunks	27
Table 11	
EANA protocol: customer dials 10XXX+0	38
Table 12	
Information digits (II)	39

Table 13	
Multifrequency receiver load capacity: 6 to 15 second holding time .	50
Table 14	
Multifrequency receiver load capacity: 16 to 25 second holding time	52
Table 15	
Multifrequency receiver requirements: Poisson 0.1 percent blocking .	54
Table 16	
Default IITP values	63
Table 17	
MFR commands	68